

Foam Extinguisher Data Sheet



	Wheeled 50L	Britannia P50 6L	FirePower 2L	FirePower 6L	FirePower 9L	Jewel 6L	Jewel 9L
Capacity (L)	50	6	2	6	9	6	9
Fire Rating		34A 183B	8A 55B	21A 144B	27A 183B	21A 144B	27A 183B
Height (mm)		570	395	560	522	520	580
Cylinder Diameter (mm)		178	112	150	190	161	183
Overall Width (mm)		189	150	300	340	180	193
Filled Weight (kg)		8.5	3.8	9.6	13.2	9.4	13.9
Range of Throw (m)		>4	>2	>4	>4	>6	>7
Duration of Discharge (secs)		40	12	30	50	14	30
Working Pressure (at 20°C)		12 bar	33 bar	15 bar	15 bar	14 bar	14 bar
Temperature Range (°C)		+5 to 60	+5 to 60	+5 to 60	+5 to 60	+5 to 60	+5 to 60
BS EN3 Approved		Yes	Yes	Yes	Yes	Yes	Yes
MED Approved	Yes	No	No	No	No	No	No
Part Number		P50F	9204/00	9234/00	9235/00	JS6LF	JS9LF
Model Number	50LMOBPT	P50FOAM	FPF2	FPRF6	FPRF9	FFEX6JSP	FFEX9JSP

Foam Extinguisher Data Sheet



	Jewel HP 6L	PowerX 1L	PowerX 2L	PowerX 3L	PowerX 6L	PowerX 9L	PowerX Multi Use 3L
Capacity (L)	6	1	2	3	6	9	3
Fire Rating	27A 183B	5A 21B	5A 34B	8A 55B	13A 144B	21A 183B	13A 70B 40F
Height (mm)	520	330	390	430	550	620	440
Cylinder Diameter (mm)	161	85	110	140	162	184	110
Overall Width (mm)	180	125	125	210	225	240	215
Filled Weight (kg)	9.4	2	3.8	5.5	9.7	13.9	5.2
Range of Throw (m)	>6	>1	>2	>2	>4	>4	>2
Duration of Discharge (secs)	19	6	6	9	15	15	13
Working Pressure (at 20°C)	14 bar	12 bar	12 bar	12 bar	12 bar	12 bar	12 bar
Temperature Range (°C)	+5 to 60	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60	-30 to 60
BS EN3 Approved	Yes	No	Yes	Yes	Yes	Yes	Yes
MED Approved	No	No	No	No	No	No	No
Part Number	JS6LF	81/03643	81/03405	81/03406	81/02903	81/02904	81/03693
Model Number	FFEXHP6JSP	F1	F2	F3	F6	F9	F3M